



|                        |   |
|------------------------|---|
| CONFIGURATIONS:        | LOW VOLTAGE (STD) OR RADIO CONTROLLED (SUFFIX -RC)  |
| MATERIALS/FINISHES:    | STAINLESS STEEL: SATIN (STANDARD) OR MIRROR POLISHED<br>BRASS: MIRROR POLISHED, OIL RUBBED OR SATIN<br>ALUMINUM: BLUE ANODIZED  |
| CONSTRUCTION:          | BACK PLATE MOUNTS TO 4" SQUARE BOX - (4S)<br>STAINLESS STEEL STUDS FURNISHED STANDARD<br>NOISE DAMPENING RUBBER CUSHIONING WASHERS<br>SUITABLE FOR OUTDOOR APPLICATIONS |
| COLOR OF LOGO/LETTERS: | BLUE, OTHER COLORS AVAILABLE  |
| SWITCH:                | UL/CSA LISTED SPDT (DPDT AVAILABLE)   |

|  |              |               |   |  |  |  |  |  |
|--|--------------|---------------|---|--|--|--|--|--|
| MATERIAL:<br><b>VARIOUS</b>                      |              |               | FINISH:<br><b>#4 SATIN</b>  |  |  | SIZE:<br><b>16 GA (0.060)</b>  |  |  |
| DIMENSIONAL TOLERANCES<br>UNLESS NOTED OTHERWISE |              |               | TITLE<br><b>PUSH PLATE</b><br><b>6" ROUND - P.T.O. &amp; LOGO</b> |  |  | CURRAN ENGINEERING COMPANY, INC.<br>28727 INDUSTRY DRIVE<br>VALENCIA, CA 91355<br>TELEPHONE (800) 643-6353<br>FACSIMILE (877) 782-5979 |  |  |
| FRAC.  | DEC.         | ANG.          |   |  |  |  |  |  |
| $\pm 1/32"$                                      | $\pm 0.031"$ | $\pm 1^\circ$ | SCALE<br><b>3/4</b>   |  |  | DRAWING NUMBER<br><b>CE-605</b>  |  |  |
| NEXT ASSY.<br><b>605-BOM</b>                     |              |               | DRAWN: <b>PSC</b> DATE <b>02/05/97</b>                            |  |  | ISSUE<br><b>1</b>  |  |  |
|  |              |               | CHECKED: <b>RDC</b> DATE <b>02/07/97</b>                          |  |  |  |  |  |
|  |              |               | APPROVED: <b>RDC</b> DATE <b>02/10/97</b>                         |  |  |  |  |  |