## 4½" Square Push Plate

with Black Surface Mount Box



## Installation

- 1) Remove flat head screw at bottom of box and separate back plate from box. Attach back plate to mounting surface using included fasteners.
- 2) Connect top of box to back plate as shown below.
- 3) Swing down and lock in place with bottom screw.



## **Part Numbers**

KIT: KIT: KIT:	 CE-KR635-318 CE-KR635-300 CE-K635	(2) Push Plates, (2) Boxes, (2) Transmitters & (1) Receiver (318MHz) (2) Push Plates, (2) Boxes, (2) Transmitters & (1) Receiver (300MHz) (2) Push Plates, (2) Boxes (Wired)	
	 CE-635-BSM-318 CE-635-BSM-300 CE-635-BSM	(1) Push Plate, (1) Box, (1) Transmitter (318 MHz) (1) Push Plate, (1) Box, (1) Transmitter (300 MHz) (1) Push Plate, (1) Box	



CURRAN ENGINEERING COMPANY, INC. 28727 INDUSTRY DRIVE

28/2/ INDUSTRY DRIVE VALENCIA, CA 91355 TELEPHONE (800) 643–6353 FACSIMILE (877) 782–5979

SIZE	DRAWING NUMBER	ISSUE
Α	21016	1