



CONFIGURATIONS:	LOW VOLTAGE (STD) OR RADIO CONTROLLED (SUFFIX -RC)
MATERIALS/FINISHES:	STAINLESS STEEL: SATIN (STANDARD) OR MIRROR POLISHED BRASS: MIRROR POLISHED, OIL RUBBED OR SATIN ALUMINUM: BLUE ANODIZED
CONSTRUCTION:	MOUNTS TO SINGLE AND DOUBLE-GANG JUNCTION BOX STAINLESS STEEL STUDS FURNISHED STANDARD NOISE DAMPENING RUBBER CUSHIONING WASHERS
COLOR OF LOGO/LETTERS:	BLUE, OTHER COLORS AVAILABLE
SWITCH:	UL/CSA LISTED SPDT (DPDT AVAILABLE)

This drawing and information is the property of Curran Engineering Co., Inc. and is considered confidential. It may not be reproduced or copied without written permission of CURRAN ENGINEERING CO., INC.

MATERIAL: STAINLESS STEEL			FINISH: #4 SATIN			SIZE: 18 GA (0.047)			
DIMENSIONAL TOLERANCES UNLESS NOTED OTHERWISE			TITLE PUSH PLATE 4-1/2" SQUARE			CURRAN ENGINEERING COMPANY, INC. 28727 INDUSTRY DRIVE VALENCIA, CA 91355 TELEPHONE (800) 643-6353 FACSIMILE (818) 782-5979			
FRAC.	DEC.	ANG.							
±1/32"	±0.031"	±1°							
SCALE FULL		NO. REQ. A/R	DRAWN: PSC		DATE 02/05/97		SIZE	DRAWING NUMBER	ISSUE
NEXT			CHECKED: RDC		DATE 02/07/97		A	CE-635-FM	1
ASSY.			APPROVED: RDC		DATE 02/10/97				