



CONFIGURATIONS:	LOW VOLTAGE (STD) OR RADIO CONTROLLED (SUFFIX -RC)
MATERIALS/FINISHES:	STAINLESS STEEL: SATIN (STANDARD) OR MIRROR POLISHED BRASS: MIRROR POLISHED, OIL RUBBED OR SATIN ALUMINUM: BLUE ANODIZED
CONSTRUCTION:	MOUNTS TO SINGLE AND DOUBLE-GANG JUNCTION BOX STAINLESS STEEL STUDS FURNISHED STANDARD NOISE DAMPENING RUBBER CUSHIONING WASHERS
COLOR OF LOGO/LETTERS:	BLUE, OTHER COLORS AVAILABLE
SWITCH:	UL/CSA LISTED SPDT (DPDT AVAILABLE)

This drawing and information is the property of Curran Engineering Co., Inc. and is considered confidential. It may not be reproduced or copied without written permission of CURRAN ENGINEERING CO., INC.

MATERIAL: STAINLESS STEEL		FINISH: #4 SATIN	SIZE: 18 GA (0.047)			
DIMENSIONAL TOLERANCES UNLESS NOTED OTHERWISE		TITLE PUSH PLATE 4-1/2" SQUARE	CURRAN ENGINEERING COMPANY, INC. 28727 INDUSTRY DRIVE VALENCIA, CA 91355 TELEPHONE (800) 643-6353 FACSIMILE (818) 782-5979			
FRAC.	DEC.					ANG.
±1/32"	±0.031"	±1°				
SCALE FULL	NO. REQ. A/R	DRAWN: PSC	DATE 02/05/97	SIZE	DRAWING NUMBER	ISSUE
NEXT ASSY.		CHECKED: RDC	DATE 02/07/97	A	CE-635-FM	1
		APPROVED: RDC	DATE 02/10/97			